

MODEL **KW-1600SPro**
1/2" N-TYPE WRENCH



Advantageous Wrench

- Compact & Light
- Hammer-Less Structure
- Low Vibration & Low Noise
- Stable Stroke
- Well - Suited to Assembly Works
and Tire Changing Works

**** 2" Long anvil also available**

**KUKEN original *N-TYPE* clutch structure resolves
all weakness of conventional impact wrenches.**

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size		12.7 mm	...	1/2 "
Capacity of Bolt Size		16 mm	...	5/8 "
Free Speed		8,000 r.p.m.		
Length (without socket)		165 mm	...	6-1/2 "
Weight (without socket)		1.46 kg	...	3.2 lbs
Air Consumption		0.30 m ³ /min	...	10.7 c.f.m.
Hose Size		6.3 mm	...	1/4 "
Air Pressure		0.62 MPa	...	90 P.S.I.



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan

Tel : +81-72-953-3346 Fax : +81-72-953-0605

Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT. No. 230822-1600S